

**AMENDMENTS TO THE CLAIMS:**

*This listing of claims will replace all prior versions, and listings, of claims in the application:*

1-8. (Canceled)

9. (Currently amended) An active matrix substrate, comprising:

a pixel electrode provided in ~~[[each]]~~ a pixel area;

~~bounded by a scanning line and a signal line that are disposed in a matrix as a whole;~~

a switching element electrically connected to the scanning line, the signal line, and the pixel electrode;

a storage capacitor electrode for ~~constituting~~ a storage capacitor; and

a storage capacitor common wire disposed parallel to the signal line so as to be electrically connected to the storage capacitor electrode, wherein

~~the storage capacitance capacitor is provided formed~~ between the pixel electrode and the storage capacitor electrode, ~~and~~

the scanning line and the storage capacitor electrode are fabricated from a same material in a single patterning; ~~and single electrode layer through patterning thereof.~~

wherein the storage capacitor electrode and the storage capacitor common wire are patterned in different steps so as to have an insulating film provided partially therebetween.

10. (Original) The active matrix substrate as defined in claim 9, wherein

the signal line and the pixel electrode are fabricated from a single conductive layer through patterning thereof.

11. (Original) The active matrix substrate as defined in claim 9, further comprising an interlayer insulation film on which the pixel electrode is provided.

12. (Currently amended) An active matrix substrate, comprising:  
a pixel electrode provided in a pixel area;  
a scanning line and a signal line;  
a switching element electrically connected to the scanning line, the signal line, and the pixel electrode;  
a storage capacitor electrode for a storage capacitor; and  
a storage capacitor common wire disposed at least partially parallel to the signal line so as to be electrically connected to the storage capacitor electrode, wherein  
storage capacitance is provided between the pixel electrode and the storage capacitor electrode,  
the scanning line and the storage capacitor electrode are fabricated from a same material in a single patterning; and  
~~The active matrix substrate as defined in claim 9, wherein the signal line, the pixel electrode, and the storage capacitor common wire are fabricated~~ of the same material in a single patterning from a single conductive layer through patterning thereof.

13. (Original) The active matrix substrate as defined in claim 9, further comprising a gate insulation film for covering a gate electrode of the switching element, wherein

the pixel electrode is disposed opposing the storage capacitor electrode across the gate insulation film.

14. (Currently amended) An active matrix substrate, comprising:  
a pixel electrode provided in a pixel area;  
a scanning line and a signal line;  
a switching element electrically connected to the scanning line, the signal line, and the pixel electrode;  
a storage capacitor electrode for a storage capacitor; and  
a storage capacitor common wire disposed at least partially parallel to the signal line so as to be electrically connected to the storage capacitor electrode, wherein  
storage capacitance is provided between the pixel electrode and the storage capacitor electrode,  
the scanning line and the storage capacitor electrode are fabricated from a same material in a single patterning;  
~~The active matrix substrate as defined in claim 9, further comprising:~~  
a protection film for covering the switching element; and  
an interlayer insulation film interposed between the pixel electrode and the protection film.

15. (Original) The active matrix substrate as defined in claim 14, wherein  
a contact hole is formed through the interlayer insulation film and the protection film so as to electrically connecting the pixel electrode to the switching element.

16-27. (Canceled)

28. (Original) The active matrix substrate as defined in claim 9, wherein the scanning line is anodized.

29-34. (Canceled)

35. (Currently amended) An image sensor, comprising:  
an active matrix substrate;  
a conversion section for converting incident magnetoelectric radiation to electric charges;  
and  
bias voltage application means for causing a storage capacitor to store the electric charges, wherein  
the active matrix substrate includes:  
a pixel electrode provided in a each pixel area; ~~bounded by~~  
a scanning line and a signal line ~~that are disposed in a matrix as a whole;~~  
a switching element electrically connected to the scanning line, the signal line, and the pixel electrode;  
a storage capacitor electrode for ~~constituting~~ a storage capacitor ~~with the pixel electrode therebetween;~~ and  
a storage capacitor common wire disposed at least partially parallel to the signal line so as to be electrically connected to the storage capacitor electrode, wherein

the signal line and the storage capacitor electrode are fabricated from a same material in a single electrode layer through patterning; and thereof

wherein the storage capacitor electrode and the storage capacitor common wire are patterned in different steps so as to have an insulating film provided partially therebetween.

36. (Original) The image sensor as defined in claim 35, further comprising:  
a gate insulation film for covering a gate electrode of the switching element; and  
a conductive body layer deposited on the gate insulation film so as to be connected to the switching element, wherein

the storage capacitor electrode and the conductive body layer constitute the storage capacitor across the gate insulation film.

37. (Original) The image sensor as defined in claim 35, wherein the scanning line is anodized.

38-41. (Canceled)

42. (New) An active matrix substrate, comprising:  
a pixel electrode provided in each pixel area bounded by a scanning line and a signal line that are disposed in a matrix as a whole;  
a switching element connected to the scanning line, the signal line, and the pixel electrode;  
a storage capacitor electrode for constituting a storage capacitor; and

a storage capacitor common wire disposed parallel to the signal line so as to be connected to the storage capacitor electrode, wherein

the storage capacitor is formed between the pixel electrode and the storage capacitor electrode,

the scanning line and the storage capacitor electrode are fabricated from a single electrode layer through patterning thereof, and

the signal line and the pixel electrode are fabricated from a single conductive layer through patterning thereof.